



Pyramid-Lok

For Use With Welded Wire Fabrics and Wire Cages

Fas-V-Lok

For 2" and 3" Mesh. Patented interlock feature that "Locks"



Pyramid-Lok Wheel-Lok and Fas-V-Lok Concrete Reinforcement Spacers

Use Pyramid-Lok Wheel-Lok and Fas-V-Lok Spacers to position mesh or spiral wound cage reinforcement during concrete production. These durable, non-corrosive plastic spacers incorporate an interlock feature that securely "locks" the spacer to the cage.

This prevents the spacers from twisting or popping off the cage when struck by form equipment. The end result is accurate cage placement and uniform concrete cover.

B E N E F I T S

- Use with precast or poured-in-place structures (i.e. pipe, manholes, slabs, floors, wall panels, box culverts and more – anywhere mesh reinforcement is required)
- Interlock feature helps eliminate spacer movement to maintain constant mesh placement and uniform concrete cover
- Easy to use, tangle free
- Virtually eliminates the rejection of product due to misplaced reinforcement – a tremendous cost savings!
- Easily snaps onto horizontal or vertical wires
- More placement versatility than other spacing alternatives
- Made of durable non-corrosive, recycled plastic
- Safe to handle – eliminates handling injuries
- Wide variety of sizes available to provide concrete cover (in 1/4" increments)

Hawkeye Pedershaab™
Concrete Technologies Worldwide

distributed by



P.O. Box 1647
697 Main Street
Tullytown, PA 19007

800-822-2565
215-547-3366 Local
215-547-5260 FAX


Pyramid-Lok, Fas-V-Lok and Wheel-Lok

Fas-V-Lok Plastic Spacers:



Part Number	Wire Diameter	Concrete Cover	Qty. Per Carton	Qty. Per Gaylord
VL-2S-1C	0.35	1"	1,500	10,000
VL-2S-X-1.25C	0.35	1.25"	1,500	10,000
VL-2S-X-1.50C	0.35	1.5"	1,500	10,000
VL-2S-X-1.75C	0.35	1.75"	1,500	10,000
VL-2S-X-2.00C	0.35	2"	1,500	10,000
VL-2S-X-2.25C	0.35	2.25"	1,500	10,000
VL-2S-X-2.50C	0.35	2.5"	1,500	10,000
VL-3S-1C	0.35	1"	1,500	10,000
VL-3S-X-1.25C	0.35	1.25"	1,500	10,000
VL-3S-X-1.50C	0.35	1.5"	1,500	10,000
VL-3S-X-1.75C	0.35	1.75"	1,500	10,000
VL-3S-X-2.00C	0.35	2"	1,500	10,000
VL-3S-X-2.25C	0.35	2.25"	1,500	10,000

Pyramid-Lok Plastic Spacers:



Part Number	Wire Diameter	Concrete Cover	Qty. Per Carton	Qty. Per Gaylord
PL-25-075	0.25	.75"	2,000	20,000
PL-25-100	0.25	1"	2,000	20,000
PL-25-125	0.25	1.25"	2,000	20,000
PL-25-150	0.25	1.5"	2,000	20,000
PL-25-175	0.25	1.75"	2,000	20,000
PL-25-200	0.25	2"	2,000	20,000
PL-35-075	0.35	.75"	1,500	15,000
PL-35-100	0.35	1"	1,500	15,000
PL-35-125	0.35	1.25"	1,500	15,000
PL-35-150	0.35	1.5"	1,500	15,000
PL-35-175	0.35	1.75"	1,500	15,000
PL-35-200	0.35	2"	1,500	15,000
PL-35-225	0.35	2.25"	1,500	15,000
PL-45-075	0.45	.75"	1,500	10,000
PL-45-100	0.45	1"	1,500	10,000
PL-45-125	0.45	1.25"	1,500	10,000
PL-45-150	0.45	1.5"	1,500	10,000
PL-45-175	0.45	1.75"	1,500	10,000
PL-45-200	0.45	2"	1,500	10,000

Wheel-Lok Plastic Spacers:



Part Number	Wire Reinforcement	Concrete Cover	Qty. Per Carton
HW-3/4-B	#1-#2 Bar	.75"	2,400
HW-1-M	Mesh	1"	500
HW-1-B	#3-#6 Bar	1"	500
HW-1-1/2-M	Mesh	1.5"	500
HW-1-1/2-SB	#2-#3 Bar	1.5"	500
HW-1-1/2-LB	#3-#6 Bar	1.5"	500
HW-2-M	Mesh	2"	300
HW-2-SB	#3-#4 Bar	2"	400
HW-2-LB	#3-#6 Bar	2"	200
HW-3-B	#3-#6 Bar	3"	100

Miscellaneous Plastic Product:

Part Description	Part Number
4" x 8" Test Cylinder with lid	HTC 4X8

distributed by



P.O. Box 1647 • 697 Main Street • Tullytown, PA 19007

800-822-2565 • 215 - 547 - 3366 www.a-lok.com