

Material Safety Data Sheet

Avanti International
822 Bay Star Blvd.
Webster, TX 77598

Chemtrec Emergency Phone: 800-424-9300
Product Data Information: 281-486-5600
Fax: 281-486-7300

Product Identification

Product Name: AV-315 MICRO FOAM

Composition/Ingredient Information

Ingredient Name / CAS Number	Exposure Limits	Concentration
2-(2-ethoxy)ethyl Acetate CAS #112-15-2	OSHA: Not established ACGIH: Not established	Trade Secret
Poly (ethylene oxide) – TDI Trimethylpropane Polymer CAS #53426-99-6	OSHA: Not Established ACGIH: Not established	Trade Secret
2,4 Toluene Diisocyanate CAS #584-84-9	OSHA PEL: 0.005 ppm ACGIH TWA: 0.005 ppm	Trade Secret
2,6 Toluene Diisocyanate CAS #91-08-7	OSHA PEL: 0.005 ppm ACGIH TWA: 0.005 ppm	Trade Secret

Hazards Information

Primary Route(s) of Entry: Skin absorption and inhalation.

Health Hazards: Severe eye irritation, severe skin and upper respiratory irritation are possible.

Eye Contact: Vapors are irritating to the eyes; with redness, tearing, blurred vision. Prolonged vapor contact may cause conjunctivitis.

Skin Contact: Exposure can cause redness swelling, scaling or blistering of the skin. Prolonged or repeated contact may cause moderate dermatitis.

Ingestion: May have corrosive effects on the lining of the mouth and stomach. May produce abdominal pain, nausea, diarrhea, and vomiting.

Inhalation: Exposure can cause upper respiratory tract irritation and pulmonary edema can occur after a serious vapor exposure; pulmonary sensitization can occur in some individuals leading to asthma like spasms of the bronchial tubes and difficulty in breathing.

First Aid Measures

Eyes: Flush with plenty of water for at least 15 minutes. Get immediate medical attention.

Skin: Wash thoroughly with soap and water. If irritation develops, consult a physician. All contaminated clothing should be washed prior to reuse.

Inhalation: Remove to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, administer oxygen and get medical attention. Asthma like symptoms may develop.

Ingestion: May have corrosive effects on the lining of the mouth and stomach; symptoms may include sore throat, abdominal pain, nausea, vomiting and diarrhea. Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Seek immediate medical attention. (Never give anything by mouth to an unconscious or convulsing person.)

Fire and Explosion Hazards

Flash Point: >212°F (100°C) COC

Flammable Limits: Not determined.

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and full protective clothing.

Unusual Fire and Explosion Hazards: Toxic fumes (carbon dioxide, carbon monoxide, carbon dioxide, nitrogen oxides, traces of cyanic acid, and TDI vapors) are released in fire situations. Downwind personnel must be evacuated.

Accidental Release Measures

Spill or Leak Procedures: Eliminate all ignition sources and evacuate spill area; with adequate ventilation, cover the spill with an inert absorbent material. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Alternately, pour water on the spill and allow reaction to occur for more than 30 minutes. Place in a proper waste container. Do not seal the drum for 48 hours to avoid possible pressure buildup. Wear respirator and other protective equipment for protection of eyes and skin during cleanup.

Handling and Storage

Storage: Store in a dry area between 64°F-86°F (18°-30°C).

Handling: Handling: Use only in well ventilated areas, unless used with recommended respiratory protection. Empty containers of this material may be hazardous when empty since they retain product residues; observe all warnings and precautions listed for the product.

Exposure Controls and Personal Protection

Respiratory Protection: Wear NIOSH approved respirator for airborne concentrations in excess of the applicable exposure limits in accordance with OSHA regulations.

Ventilation: Mechanical general/local exhaust to control vapor or mist below maximum exposure limits.

Protective Clothing: Wear impervious clothing, including boots, gloves, lab coat, apron or coveralls.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain an eye wash fountain and quick drench facilities in the work area.

Other Protective Equipment: Use impervious rubber gloves and boots.

Work/Hygienic Practices: Wash with soap and water after handling. Remove contaminated clothing and wash before next use.

Physical and Chemical Properties

Appearance and Odor: Pale yellow liquid, slightly sweet odor.

Boiling Point: 537 °F (281 °C)

Vapor Pressure (mm Hg @ 25°C): <10.5

Vapor Density: 6:1

Specific Gravity (water=1): 1.07 (+0.005)

Melting Point: Not Determined

Evaporation Rate (butyl acetate): Not Determined

Solubility in Water: Soluble, reacts rapidly with water to liberate carbon dioxide gas.

Stability and Reactivity

Stability: Stable in sealed containers.

Incompatibility (materials to avoid): Water, amines, strong bases and alcohols.

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, carbon dioxide, nitrogen oxides, traces of cyanic acid, and TDI vapors.

Polymerization: Can occur in contact with moisture, other materials that react with isocyanates, or at temperatures around 400 °F (204 °C)

Toxicological Information

Carcinogenicity: NTP and IARC consider Toluene Diisocyanate a potential carcinogen

IARC monographs:

Teratogenicity: None Determined

Reproductive Toxicity: Not Determined

Mutagenicity: None Determined

Synergistic products: None

OSHA regulated: Yes

Ecological Information

None listed.

Disposal Considerations

Dispose of in accordance with local, state, and federal regulations.

Transport Information

Proper Shipping Name: Non-Regulated Caulking Compound
 DOT Hazard Classification: None
 UN/NA Number: None
 Packaging Group: None
 Freight Class:
 DOT Labels Required: None
 DOT Placards Required: None

Regulatory Information

	TSCA	SARA 302 RQ	SARA 302 TPQ	SARA 313 LIST	CERCLA	RCRA 261.33	TSCA 8(d)
2-(2-ethoxy)ethyl Acetate (112-15-2)	NO	NO	NO	NO	NO	NO	NO
Poly (ethylene oxide) - TDI Trimethylpropane Polymer (53426-99-6)	NO	NO	NO	NO	NO	NO	NO
2,4 Toluene Diisocyanate (584-84-9)	YES	100		YES	YES	U223	YES
2,6 Toluene Diisocyanate (91-08-7)	YES	100		YES	YES	U223	YES

Other Information

The information on this MSDS is accurate to the best of Avanti International's knowledge. Avanti International makes no expressed or implied warranty, and in no case shall be liable for consequential, special, or indirect damages resulting from the use or handling of this product.